

# Selection Guide

## Total Power Factor Correction (TPFC System – APF + SVG)

# Selection Guide

## Total Power Factor Correction (TPFC System – APF + SVG)

*The Total Power Factor Correction (TPFC) system utilises the modular design of the Delta APF and SVG to combine displacement and distortion power factor correction in a single cabinet.*

Whilst an APF does provide a level of power factor correction in addition to harmonic mitigation, it is generally not economically viable to solely rely upon a harmonic filter to correct significant reactive power at a site. The TPFC serves as an all-in-one solution to boost the true power factor of an electrical network.

There are five steps in selecting the right system for you.

This guide also includes CT and breaker cable selection guides which are critical components in the installation and operation of the system.



## Step 1

### How much reactive power (kVAr) and distortion power (A) compensation is required?

To determine the amount of compensation required for an existing site you will ideally have the following information:

- Existing power factor
- Total load kVA
- New target power factor
- Total harmonic current distortion (THID) in Amperes (A) under load conditions
- New target THID level in Amperes (A) under load conditions

Existing power factor and total load kVA may already be available via your electricity bill or can be requested from your energy retailer as part of your meter data. The THID is generally available on advanced energy meters or multi-function power meters. As the harmonics vary according to the load profile throughout the day/week, the measurements should be taken under different load conditions to get the compensation current.

The best way to determine the compensation size required for a TPFC system is to have a power quality audit conducted at the site. NHP's technical team can assist with sizing up an appropriate system in accordance with the project details and organize a power quality audit. A detailed report on site power quality is provided with suggested solutions.

For sites in the design and construction stage, required compensation can be calculated using tools such as Power-Cad or other vendor tools. Please contact NHP for assistance with this.

## Step 2

### How much spare capacity is required?

As previously mentioned, the power quality on a site can change with the type and number of loads that are running. If you plan to expand your site, add equipment, or replace existing products, including slots for spare capacity would be beneficial as a future proof option.

---

#### Important Note

Even though high kVAr can be a burden on supply and electricity costs, inductive loads such as motors and welding equipment need some kVAr to maintain electromagnetic fields required to operate.

## Step 3

### 3 wire or 4 wire?

The four-wire option is required when there is an imbalance in the network.

Network imbalance is when differing line voltages across phases occurs, caused by unbalanced loads and single phase and phase-to-phase connections. This information can be found on your energy meter or power quality audit report.

	Use	Applicable industry examples
3 Wire	For balanced networks	Mining
		Industrial
		Food and beverage Manufacturing
4 Wire	For an unbalanced network with a fully rated neutral wire	Commercial
		Office
		Education Shopping centers

## Step 4

### IP rating requirement?

The environment that the cabinet would be installed has a major impact on the IP rating. NHP offers options for IP30 or IP54 floor standing cabinets and an IP31 wall mount module. It is not recommended for any of the IP rated cabinets to be installed outdoors with direct sunlight or without cover for rain.

## Step 5

### Colour of cabinet

RAL7035 Light Grey or X15 Orange.

# Ordering Guide

## Modules

Module Type	Output	3 wire or 4 wire	Catalogue No.
APF	100A	3 Wire	PQ APFM 100 X G 3 F FC X 1A
SVG	100kVAr		PQ SVGM 100 X G 3 F FC X 1A
APF	100A	4 Wire	PQ APFM 100 X G 4 F FC X 1A
SVG	100kVAr		PQ SVGM 100 X G 4 F FC X 1A

## Cabinet

Max. Number of Modules	IP rating	Colour	Catalogue No.
2	30	Grey	PQ SVGC 200 30 G X F FC X 1A
5			PQ SVGC 500 30 G X F FC X 1A
7			PQ SVGC 700 30 G X F FC X 1A
3	54		PQ SVGC 300 54 G X F FC X 1A
2	30	Orange	PQ SVGC 200 30 O X F FC X 1A
5			PQ SVGC 500 30 O X F FC X 1A
7			PQ SVGC 700 30 O X F FC X 1A
3	54		PQ SVGC 300 54 O X F FC X 1A

Note Draw type modules and cabinets are also available on a non-stocked basis. For selection, please contact NHP.

## Ordering Examples

### Example 1

To get a 200A and 300kVAr TPFC system, for a 4-wire installation, with an IP30 Grey cabinet and 20% spare capacity.

#### Order

2 x PQ APFM 100 X G 4 F FC X 1A,  
3 x PQ SVGM 100 X G 4 F FC X 1A and  
1 x PQ SVGC 700 30 G X F FC X 1A

### Example 2

To get a 200A and 100kVAr TPFC system, for a 3-wire installation, with an IP54 Orange cabinet.

#### Order

2 x PQ APFM 100 X G 3 F FC X 1A,  
1 x PQ SVGM 100 X G 3 F FC X 1A and  
1 x PQ SVGC 300 54 O X F FC X 1A

# Power Quality Commissioning Services

**FREE EXTENDED WARRANTY** for all NHP Power Quality systems when commissioned by NHP Service team

- Standard 12-month warranty is provided with all NHP Power Quality systems
- Systems commissioned by NHP service team will receive an additional 12 months warranty

It is critical that your power quality system is installed, connected, and commissioned to ensure correct and reliable operation.

## Common issues when equipment is not commissioned properly

- System performance compromised - inability to reach and maintain target power factor and reduce onsite harmonics. This can also impact your energy bills, particularly where kVA and kVA<sub>r</sub> tariffs are in place.
- Incorrect operation of power quality equipment with potential impact on other onsite equipment
- Reduced equipment operating life
- Void of equipment warranty



---

### Please note

Commissioning outside metropolitan areas may incur "Additional Travel and Accommodation Cost".

Please contact [service@nhp.com.au](mailto:service@nhp.com.au) or 1300 NHP NHP

# Cable and breaker Selection Guide

Appropriate cable and breaker selection are a vital part of ensuring the system will operate at its optimal capacity. Selection of each depends on the dominant power quality correction type of the TPF. For example, for a system with more APF modules than SVG, use the APF cable and breaker selection table with total module quantity as a guide. Circuit breaker and cable size should be based on the maximum desired size of future expansion.

## Example 1

A system with 200A and 100kVAr compensation, uses 3 power modules. Since APF is the dominant module type, we can select from the APF selection tables for a 300A APF system.

From the tables it is seen that a 500A breaker and a minimum conductor size of 120mm<sup>2</sup> is required for power and PE cables.

## Example 2

A system with 200A and 200kVAr compensation, uses 4 power modules. Since there is no dominant module type, we can select from the SVG selection table for a 400kVAr SVG system.

From the table it is seen that an 800A breaker and a minimum conductor size of 2x185mm<sup>2</sup> is required power and PE cable.

*Note: The cable sizes are a guide only, always refer to AS/NZS3008 for specific requirements. Individual de-rating based on method of installation, cable lengths, volt drop, ambient temperature and cable configuration must be allowed for when sizing cable.*

## APF Cable and breaker selection table

PM Quantity	APF Rated Current (A)	MCCB Rated Current (A)	Min. Conductor Size R/S/T/N Phases	Min. Conductor Size PE
1	100A	160A	70mm <sup>2</sup>	35mm <sup>2</sup>
2	200A	315A	150mm <sup>2</sup>	70mm <sup>2</sup>
3	300A	500A	2x120mm <sup>2</sup>	120mm <sup>2</sup>
4	400A	630A	2x150mm <sup>2</sup>	150mm <sup>2</sup>
5	500A	800A	2x240mm <sup>2</sup>	240mm <sup>2</sup>
6	600A	1000A (Suggesting 2*500A)	2x300mm <sup>2</sup>	300mm <sup>2</sup>
7	700A	1130A (Suggesting 500A+630A)	2x300mm <sup>2</sup>	300mm <sup>2</sup>

## SVG Cable and breaker selection table

PM Quantity	SVG Capacity (kVAr)	SVG Rated Current (A) @400V	MCCB Rated Current (A)	Min. Conductor Size R/S/T/N Phases	Min. Conductor Size PE
1	100kVAr	150A	180A	70mm <sup>2</sup>	25mm <sup>2</sup>
2	200kVAr	300A	350A	150mm <sup>2</sup>	50mm <sup>2</sup>
3	300kVAr	450A	550A	2x120mm <sup>2</sup>	95mm <sup>2</sup>
4	400kVAr	600A	800A	2x185mm <sup>2</sup>	150mm <sup>2</sup>
5	500kVAr	750A	900A (Suggesting 400A+630A)	2x240mm <sup>2</sup>	185mm <sup>2</sup>
6	600kVAr	900A	1100A (Suggesting 550+550A)	2x300mm <sup>2</sup>	240mm <sup>2</sup>
7	700kVAr	1050A	1250A (Suggesting 630A+630A)	2x300mm <sup>2</sup>	240mm <sup>2</sup>

### Note

For 3P3W TPFC, there are cooling fans in the cabinet, and rated voltage of these fans is AC220V, so a 1.5mm<sup>2</sup> cable should be connected to 3P3W TPFC cabinet's Neutral terminal powering AC220V fans in the cabinet. For 3P4W TPFC, Neutral cable diameter should follow the guideline in the above table.

# CT Selection Guide


The correct CTs must be selected according to the electrical condition of the installation site. NHP can provide recommendations on the correct CT and wire size to suit your application.

## Critical Installation Information

The placement of the CTs during the installation is critical to the operation of the system. This section outlines the placement options for different applications.

These guides are for the most common installations. Like the APF systems, the CT placements are the same for both balanced and unbalanced loads. For application where more than one TPFC unit is required, capacitor banks are present and any other variations to these scenarios outlined below please refer to the full CT selection and installation guide.

*Note: The TPFC system follows the same CT placement as the APF systems. The cabinets are referred to as TPFC cabinets in the drawings for simplicity. When placing orders, the cabinets will be APF or SVG cabinets depending on the system type.*



For more information on our range of CTs please use our CT Selection Guide.




# External CT Connection Guide – Single TPFC System


## 1. Closed loop

In this scenario, 3 CTs shall be installed at grid side (R/S/T phases), and another 3 CTs shall be installed at TPFC input side. All the CTs P1 should be facing grid side with same CT ratio.

Refer to Figures 1-1 and 1-2 for single line diagram (SLD) and detailed connection.



**Figure 1-1**  
CT Connection for closed loop, without cap bank scenario – SLD



**Figure 1-2**  
CT Connection for closed loop, without cap bank scenario – details


If CT connection is following this pattern, CT related parameters should be set according to following two tables for Touch Screen HMI.

## Corresponding CT settings in Touch Screen HMI


Setting Location	Setting Value
CT Setting → CT Position	Load Side
CT Setting → CT Direction	Positive
CT Setting → CT Number	3-CT
CT Setting → 1-CT Location	No need to set
CT Setting → CT Ratio	Actual CT ratio

## 2. Open loop

In this scenario, 3 CTs shall be installed at the load side (R/S/T phases), P1 should be facing the grid side. Refer to Figures 2-1 and 2-2 for single line diagram (SLD) and detailed connection.



**Figure 2 -1**  
CT Connection for open loop, without cap bank scenario – SLD



**Figure 2-2**  
CT Connection for open loop, without cap bank scenario – details

If CT connection is following this pattern, CT related parameters should be set according to following tables for Touch Screen HMI.

## Corresponding CT settings in Touch Screen HMI

Setting Location	Setting Value
CT Setting → CT Position	Load Side
CT Setting → CT Direction	Positive
CT Setting → CT Number	3-CT
CT Setting → 1-CT Location	No need to set
CT Setting → CT Ratio	Actual CT ratio

# Technical specifications

Rated Voltage	SVG AC 415 V		APF AC 415V			APF AC 690V
Input Voltage Range	AC 308V~480V					AC 432V~880V
Electric Connection	3P3W / 3P4W					3P3W
Rated Frequency	50(60)Hz ±10%					
Input Voltage THD Range	≤15%					
Rated Capacity per Module	50kVAr	100kVAr	50Amp	75Amp	100Amp	100Amp
Rated Current per Cabinet	50~700kVAr (module combination)		50~700Amp (module combination)			100~500Amp (module combination)
Redundancy	Each module is an independent reactive compensation system		Each module is an independent filtering system			
Harmonic Elimination Range	NA		2nd ~ 50th order (selectable)		2nd ~ 31st order (selectable)	
Harmonic Filtering Degree	NA		0 - 100% programmable per harmonic in Ampere value			
Harmonic Filtering Performance	NA		Filter up to 98% harmonics at rated load, THDV<3%, THDi<5% after filtering			
Reactive Power Compensation Capability	Both inductive and capacitive reactive power					
Reactive Power Compensation Performance	Cosφ ≥ 0.99 after compensation (if the SVG capacity is sufficient)		Cosφ ≥ 0.99 after compensatio (if the APF capacity is sufficient)			
Imbalance Correction Capability	Mitigate negative and zero sequence					
Full Response Time	<20ms					
Instant Response Time	<100us					
Thermal Loss	≤3% of SVG rated capacity		≤3% of APF rated capacity (KVA)			
Output Current Limitation	Automatic (100% rated capacity)					
Parallel Expansion (System)	Up to 10 Cabinets in parallel (max. 7 modules per cabinet)					Up to 10 Cabinets in parallel (5 modules per cabinet)
MTBF	>100,000 hours					
<b>Control Technology</b>	Switching Frequency	30kHz	60kHz	30kHz	20kHz	
	Controller	DSP control				
	Communication	Modbus Protocol, RS232/485				
	Monitoring	Via webserver				
<b>Physical Specifications</b>	IP Grade of Cabinet	IP30, IP54 available				
	Cooling method	Intelligent forced air cooling				
	Noise Level	< 60dB(A) @1m (Module)		< 65dB(A) @1m (Module)		< 70dB(A) @1m (Module)
	Dust Filter	Optional				
	Weights (kg)	30	57	41	63	78
	Dimensions (WxHxD) mm	440 x 174 x 600	600 x 190 x 606	440 x 174 x 522	605 x 220 x 728.2	606 x 270 x 728
<b>Environmental Requirement</b>	Ambient Temperature	-10~50°C				
	Relative Humidity	0~95%				
	Altitude	≤1000m rated capacity, 1000~2000m(derating 1% per 100m)				

The NHP logo consists of the letters 'NHP' in a bold, white, sans-serif font, centered within a dark blue square background.

**NHP**

nhp.com.au  
SALES 1300 NHP NHP  
sales@nhp.com.au

nhp-nz.com  
SALES 0800 NHP NHP  
sales@nhp-nz.com

**NHP Electrical Engineering Products**

A.B.N. 84 004 304 812  
© COPYRIGHT NHP 2020  
NHP6BCH 11/20